

EBS Ai Application Logon Request

Tag 35-MessageType=BE

Tag	Tag Name	Req	Type	Enumeration	Description
EBS Ai Standard Header		Y		35=BE	
1129	CstmApplVerID	Y	String	Valid values: 1.6, 1.7, 1.8, 2.0 and 2.1	<i>A client logging in with a version different from what is stated will result in a protocol violation user response message and the client will be disconnected</i> <i>These system behaviors are not applicable:</i> <i>version 1.6 iceberg orders support</i> <i>version 1.6 mid PD available based on floor configuration</i> <i>version 1.6 user response will not include IcebergRandomTimeIncrement and IcebergMaxRandomTime</i> <i>version 1.7 mid PD support available</i> <i>version 2.0 support for NDF Fix Outright, NDF Swap, eFix and support for MiFID reporting requirements</i>
923	UserRequestID	Y	String		Correlation Id created by the user and used to track other messages associated with this request
924	UserRequestType	Y	Integer	Valid value: 1	Log On User <i>A client logging in with a different value from what is stated will result in a protocol violation user response message and the client will be disconnected</i>
553	Username	Y	String		<i>An invalid username will not result in the client being disconnected. An error message will be returned to the client</i> <i>Assumption is that a single EBS Ai instance will not support multiple traders and only a single trader</i>
554	Password	Y	String		Associated password for the Trader ID used by the EBS Ai Server. 8—16 characters. Not Case sensitive.
5976	NoUserData	N	NumInGroup	Valid value: 1-18	Number of repeating blocks to follow
5977	UserDataName	N	String		Valid Values: AutoCancelDuplSession – "Y" or "N" SendConfirmedDeals – "Y" or "N" LargeDifferenceCheck – "Y" or "N" PriceCheck – "Y" or "N" WideSpreadCheck – "Y" or "N" HideMyPrices – "Y" or "N" OrderThroughput – integer value assume java long and if invalid value like string is provided or alphanumeric then ignore ClientType – "1,2,3,4,5,6" – if an invalid value is provided, the logon request will be reject AggregationProvider – free form text of 75 characters – an entry greater than 75 characters will result in rejection of the logon request dealcode – string of 4 characters; not validated for data type or length AllowFixingInfo – "Y" or "N" AllowFixPointsInfo – "Y" or "N" AllowNDFSwapInfo – "Y" or "N" AllowMidPx – "Y" or "N" AllowExecRegionInfo – "Y" or "N" AllowAFOKInfo – "Y" or "N" AllowPCGrossCreditEvents – "Y" or "N" AllowPCNettedCreditEvents – "Y" or "N" <i>For Boolean parameters, any values other than Y or N will be rejected and will result in a Protocol Violation Exception error being sent back in the Logon Response</i> <i>Note: Parameter names that are unknown or misspelled will be ignored by the EBS Ai Server</i>

5978	UserDataValue	N	String		Required if NoUserData > 0 Each block will contain the value for the parameter specified by the keyword in UserDataName (tag 5977).
EBS Ai Standard Trailer					